

## PARTS LIST #25 GUYED TVRO TOWERS

A.N.S.I. 70 M.P.H. Basic Wind, Exposure B
Designed to Support Maximum Load Of 6' Diameter Dish
48.9 Sq. Ft. Maximum Effective Projected Area

Part Number	Description	Tower Height					
		30′	40′	50′	60′	70′	80′
25G	Tower Section	3	4	5	6	7	8
SB25G	Short Base Section	1	1	1	1	1	1
25TDMKD	Top Dish Mount	1	1	1	1	1	1
GA25GD	Guy Assembly			1	1	1	1
3/16 EHS	Guy Wire	150′	150′	300′	400′	450′	200′
1/4EHS	Guy Wire						300′
BG2142	Big Grip	6	6	12	12	12	6
BG2144	Big Grip						6
5/16THH	Thimble	6	6	12	12	12	6
3/8THH	Thimble						6
3/85	Shackle	3	3	6	6	6	3
1/2S	Shackle						3
3/8TBE&E	Turnbuckle			6	6	6	3
1/2TBE&E	Turnbuckle						3
5/8TBE&J	Turnbuckle	3	3				
GAR30	Anchor	3	3				
GAC303	Anchor			3	3	3	3
AGK1	Anchor Grounding Kit	1	1	1	1	1	1
BGK3	Base Grounding Kit	2	2	2	2	2	2
340028	Ground Guy Clamp	3	3	6	6	6	6
TBSAFETY	Turnbuckle Safety	3	3	3	3	3	3
ACWS	Anti-Climb Warning Sign	1	1	1	1	1	1

Note: Mounting pipe is not included and must be ordered as a separate item. See Drawing C850314 for further details.

All types of antenna installations should be thoroughly inspected by qualified personnel and re-marked with hazard and warning labels at least twice a year to insure safety and proper performance.