

PARTS LIST #45 GUYED TVRO TOWERS

A.N.S.I. 70 M.P.H. Basic Wind, Exposure B
Designed to Support Maximum Load of 8' Diameter Dish
87 Sq. Ft. Maximum Effective Projected Area

| Part Number | Description | Tower Height | | | | | |
|-------------|----------------------|--------------|------|------|------|------|------|
| | | 30′ | 40′ | 50′ | 60′ | 70′ | 80′ |
| 45G | Tower Section | 3 | 4 | 5 | 6 | 7 | 8 |
| SB45G | Short Base Section | 1 | 1 | 1 | 1 | 1 | 1 |
| 45TDMKD | Top Dish Mount | 1 | 1 | 1 | 1 | 1 | 1 |
| GA45GD | Guy Assembly | | | 1 | 1 | 1 | 1 |
| 3/16EHS | Guy Wire | 150′ | | 150′ | 150′ | 200′ | 200′ |
| 1/4EHS | Guy Wire | | 150′ | 200′ | 250′ | 300′ | 300′ |
| BG2142 | Big Grip | 6 | | 6 | 6 | 6 | 6 |
| BG2144 | Big Grip | | 6 | 6 | 6 | 6 | 6 |
| 5/16THH | Thimble | 6 | | 6 | 6 | 6 | 6 |
| 3/8THH | Thimble | | 6 | 6 | 6 | 6 | 6 |
| 3/8\$ | Shackle | 3 | | 3 | 3 | 3 | 3 |
| 1/28 | Shackle | | 3 | 3 | 3 | 3 | 3 |
| 3/8TBE&E | Turnbuckle | | | 3 | 3 | 3 | 3 |
| 1/2TBE&E | Turnbuckle | | | 3 | 3 | 3 | 3 |
| 5/8TBE&J | Turnbuckle | 3 | 3 | | | | |
| GAR30 | Anchor | 3 | 3 | | | | |
| GAC303 | Anchor | | | 3 | 3 | 3 | 3 |
| AGK1 | Anchor Grounding Kit | 1 | 1 | 1 | 1 | 1 | 1 |
| BGK3 | Base Grounding Kit | 2 | 2 | 2 | 2 | 2 | 2 |
| 340028 | Ground Guy Clamp | 3 | 3 | 6 | 6 | 6 | 6 |
| TBSAFETY | Turnbuckle Safety | 3 | 3 | 3 | 3 | 3 | 3 |

Note: Mounting pipe is not included and must be ordered as a separate item. See Drawing C850315 for further details.

Installation information and a safety package (part number ACWS) are also included with the tower material. This package consists of one anti-climb warning sign and two Danger – Watch for Wires labels along with other printed safety information.

All types of antenna installations should be thoroughly inspected by qualified personnel and re-marked with hazard and warning labels at least twice a year to insure safety and proper performance.