## PARTS LIST #55 GUYED TVRO TOWERS

## A.N.S.I. 70 M.P.H. Basic Wind, Exposure B Designed to Support Maximum Load of 10' Diameter Solid, Grid, or Mesh Dish 94 Sq. Ft. Maximum Projected Area at Top of Tower

Part Number	Description	Tower Height					
		30′	40′	50′	60′	70′	80′
55G	Tower Section	3	4	5	6	7	8
SB55G	Short Base Section	1	1	1	1	1	1
55TDMKD	Top Dish Mount	1	1	1	1	1	1
GA55GD	Guy Assembly			1	1	1	1
3/16EHS	Guy Wire			150′	1.50′	200′	200′
1/4EHS	Guy Wire	150′	150′	200′			
5/16EHS	Guy Wire				250′	300′	300′
BG2142	Big Grip			6	6	6	6
BG2144	Big Grip	6	6	6			
BG2146	Big Grip				6	6	6
5/16THH	Thimble			6	6	6	6
3/8THH	Thimble	6	6	6			
7/16THH	Thimble				6	6	6
3/85	Shackle			3	3	3	3
1/25	Shackle	3	3	3	3	3	3
1/2TBE&J	Turnbuckle			6	3	3	3
5/8TBE&J	Turnbuckle	3	3		3	3	3
GAR30	Anchor	3	3				
GAC3455	Anchor			3	3	3	3
AGK1	Anchor Grounding Kit	1	1	1	1	1	1
BGK2	Base Grounding Kit	2	2	2	2	2	2
340028	Ground Guy Clamp	3	3	6	6	6	6
TBSAFETY	Turnbuckle Safety	3	3	3	3	3	3

**Note:** Mounting pipe is not included and must be ordered as a separate item. See Drawing C850316 for further details.

Installation information and a safety package (part number ACWS) are also included with the tower material. This package consists of one anti-climb warning sign and two Danger – Watch for Wires labels along with other printed safety information.

All types of antenna installations should be thoroughly inspected by qualified personnel and re-marked with hazard and warning labels at least twice a year to insure safety and proper performance.