



### TYPICAL ROOF INSTALLATION

\* USE (Ø)1/2" THREADED RODS TO SECURE MOUNT.

### TYPICAL WALL INSTALLATION

ASSY. NO.	THREADED ROD PART NO.	DESCRIPTION
HMK14	210255G	1/2"-13X14" LONG FULL THREADED ROD
HMK18	210256G	1/2"-13X18" LONG FULL THREADED ROD
HMK24	210257G	1/2"-13X24" LONG FULL THREADED ROD

QTY	PART NO.	WRITTEN DESCRIPTION	PICTORIAL DESCRIPTION
8	SEE ASSY. NO. CHART	1/2"-13 FULL THREADED ROD	
1	380163	3 OZ. TUBE OF SILICONE RUBBER SEALANT	
16	230013	1/2"-13 HVY HEX NUT	
16	230011	1/2" PALNUT	
16	250035G	1/2" STD WASHER	

**NOTES**

- 1 TO INSURE SAFETY, NO INSTALLATION, ROOF OR WALL, SHOULD BE ATTEMPTED WITHOUT A LOCAL PROFESSIONAL STRUCTURAL ANALYSIS.
- 2 IT IS THE PURCHASER'S RESPONSIBILITY TO VERIFY THAT HIS INSTALLATION IS ADEQUATE TO WITHSTAND ALL LOADS IMPOSED BY HIS MOUNT AND ANTENNA.
- 3 LOCAL ZONING AND/OR BUILDING CODES AND INSURANCE COMPANIES MAY REQUIRE AN ARCHITECT OR STRUCTURAL ENGINEER APPROVAL PRIOR TO INSTALLATION.
- 4 INSPECT MOUNT AND ANTENNA INSTALLATION EVERY 6 MONTHS (OR AFTER EVERY STORM) FOR TIGHTNESS.
- 5 ALL ANTENNA INSTALLATION SHOULD BE GROUNDED, BY THE INSTALLER, TO MEET ALL APPLICABLE CODES.
- 6 ADDITIONAL SEALANT MAY BE PURCHASED AT A HARDWARE/BUILDING CENTER.
- 7 HARDWARE IS HOT DIP GALVANIZED AFTER FABRICATION.
- \* 8 THICKER WALLS (CONCRETE, CEMENT BLOCKS, ETC.) MAY REQUIRE LONGER RODS - SEE "ROHN" CATALOG.

**UNR-Rohn**  
 HARDWARE MOUNTING KIT

Scale: 3/4" = 1'-0"  
 Part No.: 3-5-85  
 Date: 3-78

Approved By: [Signature]  
 Drawing Number: D850019 RI