



## Broadband Pole Design Properties

### 70 Ft. AGL Standard Tapered Steel Poles

Physical Properties for 70 Ft. Tapered Steel Poles			
	Light	Medium	Heavy
Design Number	T70LA	T70MA	T70HA
Tip OD, in.	6.50	9.00	12.00
OD @ grade, in.	16.20	18.70	21.70
Butt OD, in.	18.54	21.33	24.62
Number Sides	12	16	18
Δ Dia, in/ft	0.1462	0.1462	0.1462
Side Taper, in/ft	0.0731	0.0731	0.0731
Embedment, ft.	16	18	20
Auger Dia, ft.	3.0	3.0	3.5
Backfill Type	Aggregate	Aggregate	Aggregate
Total Length, ft.	86	88	90
Bare Pole Wt, lbs.	2,346	2,899	3,596
No. of Sections	2	2	2

EPA (ft <sup>2</sup> ) for 70 Ft. Tapered Steel Poles										
Wind Speed, MPH		Light			Medium			Heavy		
Fastest Mile	3-sec Gust	Sway Limit			Sway Limit			Sway Limit		
		4°	3°	2°	4°	3°	2°	4°	3°	2°
70	85	42	28	13	89	63	36	137	129	81
80	100	42	28	13	63	63	36	98	98	81
90	110	28	28	13	43	43	36	72	73	73
100	120	17	17	13	29	29	29	53	53	53
110	130	9	9	9	19	19	19	39	39	39
120	140	3	3	3	10	10	10	28	28	28

#### Notes

1. The tabulated EPA values represent the total EPA capacity of the pole. The capacity is based on the assumption that 80% of the total EPA is located at the top of the pole and the remaining 20% is located 20 ft. below the top. When all loading is located at the top of the pole, the tabulated EPA capacity must be reduced by 20%. Refer to *Antenna Index* for the EPA values and sway limitations for specific antenna types.
2. The dash (—) in the table indicates that the pole is not adequate to support antennas for the indicated wind speed.
3. Bare pole weight represents the weight of the pole without accessories.
4. Designs are based on a maximum of (6) ½" internally routed coax per elevation, 90 lbs per elevation for mounts, and antenna weights in pounds equal to 6 times the tabulated EPA values.
5. Pole embedment is based on ANSI/TIA/EIA-222-F normal soil conditions.

Designed By: Man  
Date: 7/31/07

Checked By: HA  
Date: 7/31/07

Approved By: HA  
Date: 7/31/07



**Broadband**  
**Pole Design Properties**  
 70 Ft. AGL Standard Tapered Steel Poles  
 Section Data

Section No.		Light	Medium	Heavy
	Design Number	T70LA	T70MA	T70HA
1 (top)	Length, ft.	39.75	42.08	44.50
	Galv. Wt., lbs	797	1,077	1,439
	Min. Splice, in.	16	20	24.5
	Max. Splice, in.	22.5	27	32.5
2 (bottom)	Length, ft.	48.00	48.00	48.00
	Galv. Wt., lbs	1,549	1,822	2,156
	Min. Splice, in.	—	—	—
	Max. Splice, in.	—	—	—

	Maximum Reactions		
	Light	Medium	Heavy
Download, kips	3.8	4.8	6.1
OTM, ft-kips	168.3	220.8	292.7
Shear, kips	4.9	5.8	6.5

Designed By: Mar  
 Date: 7/31/07

Checked By: HA  
 Date: 7/31/07

Approved By: HA  
 Date: 7/31/07

7/31/2007

A070102R1-2B