



ROHN EQUIPMENT SHELTER ACCESSORIES

The following are options for Rohn Equipment Shelters.

Part Number	Description	Wt.
Reinforced Floor For Batteries and Generators:		
ESFLRIN	Reinforce 8' of Shelter Floor with 4x4 Joists on 8' Centers (For Use on All Widths of Shelters)	150
Exterior and Interior Doors:		
ESP3	3'0" x 7'0" Reinforced Insulated Aluminum Door, Mill Finish, with 3 Point Locking System	106
ESP289	3'0" x 7'0" Reinforced Insulated Aluminum Door with Bullet Resistant Liner (30.06 Ballistic Resistant at 150') and 3 Point Locking System	350
ESP147	3'6" x 7'0" Reinforced Insulated Aluminum Door, Mill Finish, with 3 Point Locking System	130
ESP290	3'6" x 7'0" Reinforced Insulated Aluminum Door with Bullet Resistant Liner (30.06 Ballistic Resistant at 150') and 3 Point Locking System	430
ESP32	3'6" x 8'0" Reinforced Insulated Aluminum Door, Mill Finish, with 3 Point Locking System	141
ESSDR	3'0" x 7'0" Aluminum Frame Steel Skin Door with Dead Bolt and Industrial Lock Set	83
ESSDR3670	3'6" x 7'0" Aluminum Frame Steel Skin Door with Dead Bolt and Industrial Lock Set	110
ESSDR6070	6'0" x 7'0" Aluminum Frame Steel Skin Double Door with Dead Bolt and Industrial Lock Set	200
ESID	3'0" x 6'8" Interior Sliding Door (Hollow Wood with Handle)	55
ESLOCKSET	Cylindrical Door Knob with Stainless Steel Finish and Replaceable Core (Best #83K7AB6A)	3
ESLOCKSETPB	Push Button Lockset with Best Lock Override (Unican # 1000-2B)	6
ESDEADBLT	Dead bolt with Stainless Steel Finish and Replaceable Core (Best #83T7K-626)	2
ESDOORCLOS	Hydraulic Door Closer with Antigust Back Check (Yale #55A-BC-SB)	8
ESDOORCLOST	Hydraulic Door Closer with Thumb Turn Hold Open (Yale #5124T-BL)	8
ESAWNING	Door Awning (56" wide x 30" Deep)	10
Exterior Options:		
ESSIDING	Exterior Aggregate Siding Finish (1/16" Chopped Fiberglass with Tan Pebble Rock Finish (+/- 1/2" total thickness) Attached to Outside of Shelter)	1-1/2 Sq Ft
ESBRICK	Exterior Brick Finish (1/16" Chopped Fiberglass with Brick Veneer Attached to Outside of Shelter)	6 Sq Ft
ESSKIRT	8" Vinyl Skirt (Mounting brackets - factory installed. Skirt - field installed.)	11/Ft
ESCOLOR	Special Color (Color chip required. Contact Rohn Sales Department for color available.)	
Note: Other exterior finishes are available. Contact Rohn Sales Department for more information.		
Bullet Resistant Material:		
Specially developed material incorporated into the walls of the shelter. Available in the following conditions:		
ESBR	For 12 Ga. Shotgun Pellets, 22 Caliber Rifle, and 357 Magnum, with Fiberglass Finish	4-1/2 Sq Ft
ESBPAGG	For 30.06 Caliber Rifle, with Exposed Aggregate Finish	15 Sq Ft
ESBPFRP	For 30.06 Caliber Rifle, with Fiberglass Finish	13 Sq Ft
Note: Contact Rohn Sales Department for detailed information on exact material to use.		
ESRPRKIT	Fiberglass Repair Kit	8
RFI/EMI Shielding:		
ESRFI	Copper Mesh Screen Wire, 18 x 14 Threads Per Inch. .011 Gauge Wire, RFI/EMI Shield with Two Grounds Installed Within Walls, Roof, Floor	1/2 Sq Ft
ESRFIGSK	RFI Door Gasket (To be used only with aluminum door)	
Interior Paneling: (optional)		
ESVB48	White Vinyl Board Paneling (4' x 8' x 3/8" Thick)	50
ESVB410	White Vinyl Board Paneling (4' x 10' x 3/8" Thick)	63
ESFB48	White Fiberglass Fire Rated Paneling (4' x 8' x 3/8" Thick)	50
ESFB410	White Fiberglass Fire Rated Paneling (4' x 10' x 3/8" Thick)	63
ESGB48	White Fiberglass Paneling (4' x 8' x 3/8" Thick)	50
ESGB410	White Fiberglass Paneling (4' x 10' x 3/8" Thick)	63
ESTELBB44	Telco Backboard 4' x 4' x 3/4" Thick)	32
ESTELBB48	Telco Backboard 4' x 8' x 3/4" Thick)	64

Shelter accessories cannot be supplied unless equipment shelter is purchased from Rohn.

Prices available upon request.