



ROHN EQUIPMENT SHELTER ACCESSORIES

<u>Part Number</u>	<u>Description</u>	<u>Wt.</u>
Lights		
ESLIGHT	Exterior Light (500 Watt with Photocell)	14
ESLIGHT150HPS	Exterior Light (150 Watt with Photocell), High Pressure Sodium	15
ESLIGHT/100	Exterior Light (100 Watt with Photocell), Vandal Resistant	10
ESLIGHT/300	Exterior Flood Light (300 Watt with Photocell)	15
ESFLGT4	48" Interior Fluorescent Light with Two 40 Watt Bulbs	7
ESFLGT4D	48" Interior Fluorescent Light with Two 40 Watt Bulbs and Diffuser	10
ESINLGT	Incandescnet Interior Light (100 Watt) with Wire Guard	5
ESINLGT200	Incandescnet Interior Light (200 Watt) with Wire Guard	6
ESEMGLT	Emergency Light (2 Head with Charger, Batteries Included)	18
ESFLGTSUP	Fluorescent Light RFI Suppressor	2
ESLIGHT/150MD	Exterior Dual Head (150 Watt) Flood Light With Molton Detector Sensor	8
ESLIGHT/70HPS	Exterior Dual Head (70 Watt With Photocell) High Pressure Sodium	7
ESTIMERSW	Timer Switch for Interior and Exterior Lights	1
Lighting Arrestors:		
ESARREST1PH	Lightning Arrestor, Single Phase (Joslyn 1250-33)	1
ESARREST3PH	Lightning Arrestor, Three Phase (Joslyn 1250-32 and 1250-33)	2
ESJOS1265/85	Lightning Arrestor, Single Phase (Joslyn 1265-85)	35
ESJOS1455/45	Lightning Arrestor, Three Phase (Joslyn 1455-45)	40
Interior Halo Grounding:		
ESHALO2	#2 Stranded Copper Wire with Green Insulation and Ceramic Standoffs	201/MFT
ESHALO2T	#2 Solid Copper Wire Tinned with Ceramic Standoffs	201/MFT
ESHALODP2T	#2 Tinned Solid Cooper Wire Drop with 8' Additional to be Connected to Exterior Ground System by Others	5
ESHALO2/0	#2/0 Stranded Copper Wire with Green Insulation and Ceramic Standoffs	411/MFT
ESHALODP2/0	#2/0 Stranded Copper Wire Drop with Green Insulation with 8' Additional to be Connected to Exterior Ground System by Others	6
ESHALO4/0	#4/0 Stranded Copper Wire with Green Insulation and Ceramic Standoffs	411/MFT
ESHALODP4/0	#4/0 Stranded Copper Wire Drop with Green Insulation with 8' Additional to be Connected to Exterior Ground System by Others	6
ESEQGRD6/2	#6 Stranded Copper Wire with Green Insulation Connected to Equipment and Crimped to a #2 Interior Halo	2
ESEQGRD6/4	#6 Stranded Copper Wire with Green Insulation Connected to Equipment and Crimped to a #2/0 or #4/0 Ground Halo	3
ESEQGRD2/2	#2 Stranded Copper Wire with Green Insulation Connected to Equipment and Crimped to a #2 Interior Halo	4
ESEQGRD2/4	#2 Stranded Copper Wire with Green Insulation Connected to Equipment and Crimped to a #2/0 or #4/0 Ground Halo	5
Alarms: (Remote Capability, either normally opened or normally closed contacts)		
ESALARMAC	High/Low Temperature Alarm (Consists of 2 Thermostats with 120 Volt AC, Dry Contacts)	3
ESALARMHUM	Humidity Alarm (Consists of 1 Humidistat, 120 Volt AC or 24 Volt DC, Dry Contacts)	4
ESSWITCH	Illegal Entry Switch (Consists of 24 Volt DC, Dry Contact)	1/2
ESSMOKDET	Smoke Detector (120 Volt, Dry Contact)	1
ESSMOKDET24	Smoke Detector (24 Volt, Dry Contact)	1
ESHEATDET	Heat Detector (120 Volt, Dry Contact)	1
ESALARMPPF	Power Failure Alarm (DPDT Dry Contacts, 240 Volt Relay)	4
ESALARMTB	Alarm Terminal Block (50 PT Telephone Wire Type) with Wire and Conduit from above Alarms to Block	5
ESKWYSWITCH	Key Switch to Override Door Alarm Contact	2
Air Conditioners: (Window Unit, Single Phase with Integral Thermostat) (Note: 12,000 BTU is the equivalent of one ton.)		
ESAC5800	6,200 BTU, 120 Volt	108
ESAC9500-115	10,200 BTU, 120 Volt	116
ESAC9500	9,700 BTU, 240 Volt	116
ESAC11400	11,200 BTU, 240 Volt	116
ESAC14700	15,000 BTU, 240 Volt	151
ESAC18500	18,000 BTU, 240 Volt	180
ESAC22900	23,000 BTU, 240 Volt	210
ESAC33000	33,000 BTU, 240 Volt	250

Shelter accessories cannot be supplied unless equipment shelter is purchased from Rohn.